



M044 AUTOMATIC MIXER WITH SAND INTRODUCTION

Used to mix mortar and cement, for the preparation of sample tested ultimate flexion/compression. It is supplied complete with electronic card for the automatic cycle EN 196. The backlit LCD display shows, each moment, at operator all stages of the preparation visualizing even any operation of the safety devices, such as emergency button and the frontal protection door. Can also work in manual mode, the display shows the time of mixing. The operator can select the minimum speed and maximum speed.

The supply included:

- N°1 Stainless bowl, which is fixed into the frame, on which it can be moved vertically by means of a handle
- N°1 Planeraty movement beater with bayonet coupling
- Front protection device with polycarbonate with safety device which ensures that the engine shut down movement of the beater, if it is raised the front
- Device for the automatic introduction of the sand during the cycle automatically
- N°1 standard sand 1350 g
- Manual instruction
- Certificate of conformity with EN 196

The accessories to effect all the tests have to be ordered separately.

TECHNICAL CHARACTERISTICS:

435 x 500 x 670 mm	Dimensions Width x Depth x Height	17.1 x 19.7 x 26.4 in.
44 kg	Weight	97 lb
+ 10 °C / + 35 °C	Operating temperature	+ 50 °F / + 90°F
140 ± 5 giri/min 62 ± 5 giri/min	Minimum speed (Slow) Minimum speed (Planetarium)	
285 ± 10 giri/min 125 ± 10 giri/min	Maximum speed (Fast) Maximum speed (Planetarium)	
4.7 l	Bowl capacity	
240V 1ph 50Hz	Power supply	

SPARE PARTS

	M043-R100 MIXING BOWL Built in steel.
---	--



M043-R101 MIXING BEATER
Built in stainless steel.



M043-R102 STANDARD SAND
Used pearl packaging test of malta 40x40x160 mm.
It is provided in sacks from 1350 g.